

INSULATED SPADE TERMINALS Y型绝缘端子 UL: E357535

PART NO 2015-2018	ITEM NO	WIRE RANGE		DIMENSIONS						
		AWG/MCM	mm <sup>2</sup>	ΦE	ΦD	Φd	W	B	L	COLOR
LY0021-1001	VF1.25-3YS	22-16	0.25-1.65	3.7	4	1.7			10.7	10.4
LY0021-1002	VF1.25-3YW			3.7	4	1.7	21.8			
LY0021-1003	VF1.25-3YSA			3.2	4	1.7	21.8			
LY0021-1004	VF1.25-4YS			4.3	4	1.7	21.8			
LY0021-1005	VF1.25-4YW			4.3	4	1.7	21.8			
LY0021-1006	VF1.25-5Y			5.3	4	1.7	21.8			
LY0021-1007	VF1.25-6Y			6.7	4	1.7	22.8			
LY0021-1008	VF2-3YS			3.7	4.6	2.3	10.7	10.4		
LY0021-1009	VF2-3YSA	3.2	4.6	2.3	21.8					
LY0021-1010	VF2-3YW	3.7	4.6	2.3	21.8					
LY0021-1011	VF2-4YS	4.3	4.6	2.3	21.8					
LY0021-1012	VF2-4YW	4.3	4.6	2.3	21.8					
LY0021-1013	VF2-5Y	5.3	4.6	2.3	21.8					
LY0021-1014	VF2-6Y	6.7	4.6	2.3	24.8					
LY0021-1015	VF3.5-4Y	12-10	2.63-4.60	4.3	5.6	3.2			10.7	10.4
LY0021-1016	VF3.5-5Y			5.3	5.6	3.2	24.8			
LY0021-1017	VF5.5-3Y	12-10	4.60-6.64	3.7	6.6	3.5	10.7	10.4	26.5	YELLOW
LY0021-1018	VF5.5-4Y			4.3	6.6	3.5			26.5	
LY0021-1019	VF5.5-5Y			5.3	6.6	3.5			26.5	
LY0021-1020	VF5.5-6Y			6.4	6.6	3.5			31.2	
LY0021-1021	VF8-5Y	8	6.64-10.52	5.3	8.3	4.5	9	17.5	32.0	RED
LY0021-1022	VF8-6Y			6.7	8.3	4.5			32.5	
LY0021-1023	VF14-5Y	6	10.52-16.78	5.3	9.7	5.9	9	17.5	40.5	RED/BLUE
LY0021-1024	VF14-6Y			6.7	9.7	5.9			40.5	

